

DATA SHEET

Model Name : RI 15261-D RF SHIELD BOX

Features :

- Trolley Based
- Rugged Aluminium Welded Box
- Fully Customizable Shielded Enclosure
- User Defined I/O Connector
- Tight Locking and Gasket System
- Copper Beryllium fingers are provided for ensuring Shielding Effectiveness.
- Powered by AC / DC Power Filter Lines.
- Honeycomb Ventilation for Cooling.



Specification:

- Exterior : 1525 mm(W) X 610 mm(H) X 890 mm(D)
- Interior : 1475 mm(W) X 560 mm(H) X 840 mm(D)
- Frequency Range : 20 MHz to 6 GHz
- Isolation: $\geq 125\text{dB @ } 1\text{GHz}$
 $> 120\text{dB @ } 3\text{GHz}$
 $> 90\text{ dB @ } 6\text{GHz}$
- Rack Mountable / Table Top / Trolley Based

Application:

- Ideal for 802.11a , b, g, n, ac.
- Bluetooth , Wi-Fi , 4G , 5G Device Testing , RFID Device Testing ,
- R & D

15, SATSANG ESTATE , NEAR SAFARI HOTEL , OPP S.P.RING ROAD , ODHAV, AHMEDABAD- 382415

GSTIN : 24ABEFR6147C1ZF E-mail : info@rfisolation.in Contact Number : 91-9974885656