

DATA SHEET

Model Name: RI 3666 RF SHIELD BOX

Features:

- Rack Mountable / Table Top
- Rugged Aluminum Welded Box
- Fully Customizable Shielded Enclosure
- User Defined I/O Connector
- Tight Locking and Gasket System
- Copper Beryllium fingers are provided for ensuring Shielding Effectiveness.
- Powered by AC / DC Power Filter Lines.
- Honeycomb Ventilation for Cooling.



Specification:

- Exterior : 360 mm(W) X 360 mm(H) X 660 mm(D)
- Interior : 310 mm(W) X 310 mm(H) X 615 mm(D)
- Frequency Range : 20 MHz to 6 GHz
- Isolation: $\geq 125\text{dB}$ @ 1GHz
 $> 120\text{dB}$ @ 3GHz
 $> 90\text{ dB}$ @ 6GHz
- Rack Mountable / Table Top
- SMA Connector with dusk Cap : 4 Nos
- Filtered USB 3.0 : 2 Nos
- AC Power 110V~245VAC : 1 Nos
- DC Power Jack (12 ~ 50VDC) : 2 Nos
- 120 x 120 mm Honeycomb Air vent : 1 Nos
- 120 x 120 mm Honeycomb Air vent WITH Exhaust Fan : 1 Nos
- Universal Socket Power Strip with 5 Power Sockets : 1 No