

# DATA SHEET

**Model Name: RI 6060 RF SHIELD BOX**

## **Features:**

- Stand alone RF Shield box
- Rugged Alluminium Welded Box
- Fully Customizable Shielded Enclosure
- Tight Locking and Gasket System
- Copper Beryllium fingers are provided for ensuring Shielding Effectiveness.
- Honeycomb Ventilation for Cooling.
- Polyurethane Absorber

## **Specification:**

- Exterior : 600 mm(W) X 600 mm (H) X 600 mm(D)
- Interior : 550 mm (W) X 550 mm(H) X 550 mm(D)
- Frequency Range : 20 MHz to 8 GHz
- Isolation:  $\geq 120$ dB @ 1GHz  
 $> 120$ dB @ 3GHz  
 $\geq 90$  dB up to 8GHz
- SMA BULKHEAD ADAPTER WITH DUST COVER : 6 Nos
- Filtered Ethernet Connector : 4 Nos
- Filtered USB 3.0 Connector : 2 Nos
- Filtered DB-9 Connector : 1 No
- Filtered HDMI Connector : 1 No
- 120 x 120 mm Honeycomb Air vent : 1 No
- 120 x 120 mm Honeycomb Air vent with Axial Fan : 1 No
- Filtered Ac Power(110/230V AC) : 1 No
- Filtered DC Power Jack : 2 Nos
- Flat Polyurethane Absorber
- Table TOP

## **Application**

- Ideal for 802.11a, b, g, n, ac.
- Bluetooth , Wi-Fi , 4G , 5G Device Testing , RFID Device Testing ,
- R & D , OTA ,Router Testing