

DATA SHEET

Model Name: RI 6253 RF SHIELD BOX

Features:

- Standalone RF Shield box
- Rugged Aluminum Welded Box
- Fully Customizable Shielded Enclosure
- Tight Locking and Gasket System
- Copper Beryllium fingers are provided for ensuring Shielding Effectiveness.
- Honeycomb Ventilation for Cooling.
- Polyurethane Absorber



Specification:

- Exterior : 625 mm(W) X 535 mm (H) X 450 mm(D)
- Interior : 575 mm (W) X 485 mm(H) X 400 mm(D)
- Frequency Range : 20 MHz to 8 GHz
- Isolation: >=120dB @ 1GHz
 >120dB @ 3GHz
 >=90 dB up to 8GHz
- SMA BULKHEAD ADAPTER WITH DUST COVER : 12 Nos
- Filtered Ethernet Connector(10M,100M,1G,10G) : 2 Nos
- Filtered USB 2.0/3.0 Connector :2 Nos
- Filtered DB-9 Connector : 1 No
- 100 x 100 mm Honeycomb Air vent : 1 No
- 100 x 100 mm Honeycomb Air vent with Axial Fan : 1 No
- Filtered Ac Power(110/230V AC) :1 No
- Filtered DC Power Jack : 2 Nos
- Flat Polyurethane Absorber
- Shielded Window – 275 mm x 120 mm
- Shielded Hand Gloves
- Table TOP